


Round flange

MF4

Type 14



Piston Ø	MM Ø	A 5)	KK 5)	A 6)	KK 6)	CH	D	DA	D4 2)	EE 4)	EE 4)	Y	X1
40	22 / 28	16	M 16x1.5	30	M 18x2	16 / 22	88	50	34	G 1/2	M 22x1.5	79	41
50	28 / 36	22	M 22x1.5	35	M 24x2	22 / 30	102	60	34	G 1/2	M 22x1.5	87	48,5
63	36 / 45	28	M 28x1.5	45	M 30x2	30 / 36	120	78	42	G 3/4	M 27x2	100	56,5
80	45 / 56	35	M 35x1.5	55	M 39x3	36 / 46	140	95	42	G 3/4	M 27x2	104	67
100	56 / 70	45	M 45x1.5	75	M 50x3	46 / 60	170	125	47	G 1	M 33x2	124	82
125	70 / 90	58	M 58x1.5	95	M 64x3	60 / 75	206	150	58	G 1 1/4	M 42x2	135	99
140	90 / 100	65	M 65x1.5	110	M 80x3	75 / 85	226	170	58	G 1 1/4	M 42x2	156	109,5
160	100 / 110	80	M 80x2	120	M 90x3	85 / 95	265	190	65	G 1 1/2	M 48x2	185	129
180	110 / 125	100	M 100x2	140	M 100x3	95 / 110	292	210	65	G 1 1/2	M 48x2	199	142,5
200	125 / 140	110	M 110x2	150	M 110x4	110 / 120	310	235	65	G 1 1/2	M 48x2	205	152
220	140 / 160	120	M 120x3	160	M 120x4	120/140	355	273	65	G 1 1/2	M 48x2	242	174
250	160 / 180	120	M 120x3	160	M 120x4	140/160	393	305	65	G 1 1/2	M 48x2	266	194
280	180 / 200	130	M 130x3	190	M 150x4	160/180	425	343	65	G 1 1/2	M 48x2	282	210
320	200 / 220	-	-	200	M 160x4	180/200	490	394	65	G 1 1/2	M 48x2	287	243

Piston Ø	MM Ø	ZP	X* min	RD	NF	WA	PJ	FB H13	VD	FC js13	UC -1	α	RA f8	VE
40	22 / 28	256	-	90	30	14	120	9	5	108	130	60°	52	40
50	28 / 36	264	-	110	30	18	120	11	5	130	160	60°	65	40
63	36 / 45	297	-	130	35	22	133	13,5	5	155	185	60°	75	45
80	45 / 56	315	-	145	35	20	146	13,5	5	170	200	60°	95	45
100	56 / 70	375	-	175	45	30	171	17,5	5	205	245	60°	115	55
125	70 / 90	432	-	210	50	32	205	22	5	245	295	60°	135	60
140	90 / 100	475	-	230	50	35	219	22	10	265	315	60°	155	70
160	100 / 110	535	-	275	60	40	240	30	10	325	385	60°	200	80
180	110 / 125	585	-	300	70	40	264	30	10	360	420	60°	220	90
200	125 / 140	615	-	320	75	40	278	33	10	375	445	60°	235	95
220	140 / 160	720	-	370	85	40	326	33	10	430	490	60°	270	115
250	160 / 180	744	-	415	85	40	326	39	10	485	555	60°	300	125
280	180 / 200	839	31	450	95	40	375	39	10	520	590	60°	325	130
320	200 / 220	935	-	510	120	40	431	45	10	600	680	60°	365	155

* Unless otherwise specified, all dimensions are given in millimetres.

MM = Piston rod Ø

X* = Stroke length

1) = Bleeding: When viewed on the piston rod, the orientation is always offset by 90° to the pipe connection (in a clockwise direction)

2) = Ø D4 max. 0,5 mm deep

3) = Throttle valve only with end position damping „E” (180° to the bleed point)

4) = For flange connections see separate table on pages 17

5) = Thread version „G”

6) = Thread version „A”

7) = Take the minimum stroke length „X*min.” into account




How to order a HYDROMAT H1 series cylinder compliant with ISO 3320

The HYDROMAT H1 series cylinders compliant with ISO 3320 standards are provided with an identification code which describes the construction specifications in a non-ambiguous way. To make up the code for the order, follow the code diagram set out below and insert the letters identifying the various features of the desired cylinder in the sequence given below.

Features	Description	Code
Series	To ISO 3320 standards	H1
	To ISO 3320 standards for taking transducer	T1
Bore	Specify bore in mm (indicate 3 figures)	-
Rod MM (diameter)	22 mm (bore 40)	F
	28 mm (bore 40 and 50)	H
	36 mm (bore 50 and 63)	L
	45 mm (bore 63 and 80)	M
	56 mm (bore 80 and 100)	P
	70 mm (bore 100 and 125)	R
	90 mm (bore 125 and 140)	T
	100 mm (bore 140 and 160)	U
	110 mm (bores 160 and 180 ⁵⁾)	V
	125 mm (bores 180 ⁵⁾ and 200)	A
	140 mm (bore 200 and 220)	Z
	160 mm (bore 220 and 250)	B
180 mm (bore 250 and 280)	X	
200 mm (bore 280 and 320)	C	
220 mm (bore 320)	Y	
Stroke	Specify the stroke in mm (indicate 4 figures)	-
Rod type	Without cushioning	C
	Front cushioning	E
	Rear cushioning ⁶⁾	G
	Cushioning on both ends ⁶⁾	P
	Double rod without cushioning	S
Double rod with cushioning	T	
Special machining	Female rod threading	W
	Customised machining	Z
Mounting type	Side foot (not in line to ISO 3320)	03
	Intermediate fixed trunnion (ISO MT4)	06
	Rear clevis (ISO MP3)	07
	Rear spherical bearing (ISO MP5)	08
	Front flange (ISO MF3)	13
Rear flange (ISO MF4)	14	

5) Bore non-compliant with ISO 3320 standard
6) Not available for bores 50 and 63 of the T1 series

Cylinder ordering code



Example of cylinder code:
H1063M0125E13


- H1 = series differential cylinder according to ISO 3320 standards
- 063 = bore 63
- M = rod 45
- 125 = stroke 125
- E = front cushioning
- 13 = front flange (ISO MF3)

The input connection and front cushioning positions are standard so they are not specified in the ordering code (oil feeding inlets side 1 on head and cap, cushioning side 3 on head as specified in Table 13. on page 43).

- When issuing the order for the cylinder, provide the following information:
- code identifying the model
 - quantity
 - special features (if requested) with any enclosed sketches and/or construction drawings
 - operating conditions for special uses
 - delivery date with type of priority

Code	Description	Features
D	Specify the position of the drainage connection	Drainage connection
K	Specify the position of the front and rear inductive sensors	Position of inductive sensors
S	Specify the position of the front and rear air bleeds	Position of air bleeds
R	Specify the position of the front and rear braking adjustment devices	Position of braking adjustment devices
P	Specify the position of front and rear connections	Position of connections
-	Specify the number of spacers (multiples of 50 mm)	Spacers
T U ¹⁾ V ²⁾ Z	Seals for water and glycol mixtures Low friction seals Seals for high temperatures and/or aggressive fluids Seals for heavy applications	Seals
D ³⁾ E ³⁾ F ³⁾	Front inductive sensor Rear inductive sensor Front and rear inductive sensor	Inductive sensors
A B C ⁴⁾	Front air bleed Rear air bleed Front and rear air bleeds	Air bleeds

1) min. working pressure 20 bar
2) max. working temperature for T1 and H1 series cylinders fitted with inductive sensors: 70 °C
3) Using inductive sensors, the cylinder must be provided with cushioning (front or rear)
4) Compulsory for T1 series cylinders



Example of cylinder code:
H1125T0800PW06 / FU P14 K22

- H1 = series differential cylinder to ISO 3320 standards
- 125 = bore 125, T = rod 90, 0800 = stroke 800
- P = cushioning on both ends
- W = female rod threading
- 06 = intermediate fixed trunnion (ISO MT4)
- F = front and rear inductive sensor
- U = low friction seals
- P = position of input connections side 1 on head and side 4 on cap
- K = position of inductive sensor side 2 on head and cap

Cushioning in standard position side 3 on head and cap (see Table 13. on page 43).